



9 Aspinall place, Mulgrave NSW 2756

Ph: 02 4545 2828

sales@jpsmetal.com.au

www.jpsmetal.com.au

UNIVERSAL BEAMS - AS/NZS GRADE 300

Description	Depth of section	Width of section	Weight (KG/M)	Flange thickness	Web thickness
150 UB 14	150 mm	75 mm	14.000	7 mm	5 mm
150 UB 18	155 mm	75 mm	18.000	9.5 mm	6 mm
180 UB 16	173 mm	90 mm	16.100	7 mm	4.5 mm
180 UB 18	175 mm	90 mm	18.100	8 mm	5 mm
180 UB 22	179 mm	90 mm	22.200	10 mm	6 mm
200 UB 18	198 mm	99 mm	18.200	7 mm	4.5 mm
200 UB 22	202 mm	133 mm	22.300	7 mm	5 mm
200 UB 25	203 mm	133 mm	25.400	7.8 mm	5.8 mm
200 UB 29	207 mm	134 mm	29.800	9.6 mm	6.3 mm
250 UB 25	248 mm	124 mm	25.700	8 mm	5 mm
250 UB 31	252 mm	146 mm	31.400	8.6 mm	6.1 mm
250 UB 37	256 mm	146 mm	37.300	10.9 mm	6.4 mm
310 UB 32	298 mm	149 mm	32.000	8 mm	5.5 mm
310 UB 40	304 mm	165 mm	40.400	10.2 mm	6.1 mm
310 UB 46	307 mm	166 mm	46.200	11.8 mm	6.7 mm
360 UB 45	352 mm	171 mm	44.700	9.7 mm	6.9 mm
360 UB 51	356 mm	171 mm	50.700	11.5 mm	7.3 mm
360 UB 57	359 mm	172 mm	56.700	13 mm	8 mm
410 UB 54	403 mm	178 mm	53.700	10.9 mm	7.6 mm
410 UB 60	406 mm	178 mm	59.700	12.8 mm	7.8 mm
460 UB 67	454 mm	190 mm	67.100	12.7 mm	8.5 mm
460 UB 74	457 mm	190 mm	74.600	14.5 mm	9.1 mm
460 UB 82	460 mm	191 mm	82.100	16 mm	9.9 mm
530 UB 82	528 mm	209 mm	82.000	13.2 mm	9.6 mm
530 UB 92	533 mm	209 mm	92.400	15.6 mm	10.2 mm
610 UB 101	602 mm	228 mm	101.000	14.8 mm	10.6 mm
610 UB 113	607 mm	228 mm	113.000	17.3 mm	11.2 mm
610 UB 125	612 mm	229 mm	125.000	19.6 mm	11.9 mm